



NOTES:

1. TORQUE RATINGS, Nm

| PART NUMBER  | SYMMETRIC TORQUE |
|--------------|------------------|
| BH12-1003-30 | 3.0              |
| BH12-1003-45 | 4.5              |

2. CYCLE LIFE:  
WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN  
±25% OF TORQUE SPECIFICATION.

3. FINISH: PLATING

4. 360 DEGREE SHAFT ROTATION

5. U.S. PAT. NO. 9,609,770

|  |   |                         |                       |                                |           |
|--|---|-------------------------|-----------------------|--------------------------------|-----------|
| <b>METRIC(MM)</b><br>0-3< ±0.15<br>3-10< ±0.20<br>10-30< ±0.25<br>30-50< ±0.30<br>50-100< ±0.40<br>100-200< ±0.50  | <b>[ENGLISH] (IN)</b><br>0-0.118<±0.006<br>0.118-0.394<±0.008<br>0.394-1.181<±0.010<br>1.181-2.000<±0.012<br>2.000-4.000<±0.016<br>4.000-8.000<±0.020 | <h1>LEEEO</h1>          |                       | <b>DWG NO.</b><br>BH12-1003-xx |           |
|  |   |                         |                       | <b>TITLE</b><br>BH12           |           |
| <b>PROPRIETY ITEM - ALL INFORMATION DISCLOSED<br/>         HEREON IS CONFIDENTIAL AND ALL RIGHTS<br/>         PATENT AND OTHERWISE ARE RESERVED BY<br/>         LEEEO TECHNOLOGIES CORPORATION</b> |   | <b>APPROVED</b><br>JLIU | <b>DRAWN</b><br>BCHEN | <b>MATERIAL</b><br>STEEL       |           |
|  |   | <b>SHEET 1 OF 1</b>     | <b>SCALE: 2.000</b>   | <b>REV</b>                     | <b>A3</b> |