



NOTES:

1. TORQUE RATINGS, Nm
SYMMETRIC TORQUE: 0.05, CW=CCW
2. CYCLE LIFE:
WITHIN 10,000 CYCLES STATIC TORQUE STAY WITHIN
±35% OF TORQUE SPECIFICATION
3. FINISH: PLATING
4. 360 DEGREE SHAFT ROTATION

METRIC(MM)	[ENGLISH] (IN)	LEEEO		DWG NO.	
0-3 ± 0.15	0-0.118 ± 0.006			BH3A-1003-01	
3-10 ± 0.20	0.118-0.394 ± 0.008	TITLE			
10-30 ± 0.25	0.394-1.181 ± 0.010	APPROVED	DRAWN	BH3A	
30-50 ± 0.30	1.181-2.000 ± 0.012	JLIU	BCHEN		
50-100 ± 0.40	2.000-4.000 ± 0.016			MATERIAL	
100-200 ± 0.50	4.000-8.000 ± 0.020			STEEL	
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION		SHEET 1 OF 1		SCALE: 5.000	REV
				A3	