



NOTES:

1. TORQUE RATINGS, Nm  
SYMMETRIC TORQUE: 0.4, CW=CCW
2. CYCLE LIFE:  
WITHIN 10,000 CYCLES STATIC TORQUE STAY WITHIN  
±25% OF TORQUE SPECIFICATION.
3. FINISH: PLATING
4. 360 DEGREE SHAFT ROTATION

METRIC(MM)	[ENGLISH] (IN)	<b>LEEEO</b>		DWG NO.	
0-3 <math>\pm 0.15</math>	0-0.118 <math>\pm 0.006</math>				
3-10 <math>\pm 0.20</math>	0.118-0.394 <math>\pm 0.008</math>	TITLE			
10-30 <math>\pm 0.25</math>	0.394-1.181 <math>\pm 0.010</math>	APPROVED	DRAWN	MATERIAL	
30-50 <math>\pm 0.30</math>	1.181-2.000 <math>\pm 0.012</math>	JLIU	BCHEN	STEEL	
50-100 <math>\pm 0.40</math>	2.000-4.000 <math>\pm 0.016</math>	SHEET 1 OF 1		REV	A3
100-200 <math>\pm 0.50</math>	4.000-8.000 <math>\pm 0.020</math>			SCALE: 3.000	
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION					